

RL 250, RL 300, RL 350

		RL 250	RL 300	RL 350
POS				
Electrical setup				
001	3x 400 V	S	S	S
002	3x 230 V motor voltage	W	W	W
004	50 Hz	S	S	S
005	60 Hz	W	W	W
007	7.5 HP (5.5 kW)* (!002)	W	-	-
008	11 PS (8.2 kW)*	-	S	-
008	11 PS (8.2 kW)* (# 3x230V)	W	-	-
009	15 PS (11 kW)*	-	-	S
10	Anti-static filter	O	O	O
16	Power and speed adjustment through pressure measurement (#001)	O	O	O
21	Version with rotary valve instead of dust pin (! 20)	O	O	O
20	Preparation for briquetting press	W	W	W
25	Equipped with extraction port on the left hand side	W	W	W
26	Powder fire extinguisher instead of water extinguisher	W	W	W
Wood chip briquetting press				
50	02.0.484 - Wood Chip Briquetting Press FBP 50 (30–50 kg/h) (#20)	O	O	O
51	02.0.485 - Wood Chip Briquetting Press FBP 60 (60–70 kg/h) (#20)	O	O	O
52	02.0.486 - Wood Chip Briquetting Press FBP 70 (70–100 kg/h) (#20)	O	O	O
53	02.0.483 - Water cooler for briquetting press	O	O	O
General				
	Max. airflow m³/h	5000	6000	8000
	Nominal air flow capacity 20 m/sec. m³/h	3540	5090	6950
	Static pressure Pa	2500	2680	2630
	Dimensions mm (L x W x H)	2640 x 1140 x 2260	2640 x 1140 x 2260	2640 x 1140 x 2260
	Filter surface area m²	50	50	71
	Extraction connector Ø in mm	250	300	350
	Dust emission quality mg/m³	<0,1	<0,1	<0,1
	Acoustic pressure dB	75	75	75
	Chip volume litres	2x 250	2x 250	2x 250
	Weight kg (with standard configuration)	825	840	880
Automatic Start				
	02.0.340 - Automatic Start for 1-8 Machines	O	O	O
	02.0.345 - Automatic Start for 1-8 Machines and 8 electric gates	O	O	O
	02.0.344 - Automatic Start for 1-8 Machines and 8 electric gates, freely programmable	O	O	O
	02.0.346 - Transformer Coils for Automatic Start	O	O	O
Important Accessories				
60	D-160 mm suction pipe for the extraction of the chips from the rotary feeder (#21)	W	W	W
	02.0.037 - 10 pcs. Chip-Bags for RL 250/300 (1200 x 500 x 1300 x 0,1 mm)	O	O	O
500	403-275 - Sound Absorber for RL 250/300/350	O	O	O