

# FW 950 classic, FW 1102 classic

# FELDER®

		FW 950 classic	FW 1102 classic
POS			
	Electrical setup		
001	3x 400 V	S	S
004	50 Hz	S	S
008	10.0 HP (7.5 kW) sanding motor for sanding module	S	-
008	20.0 HP (15.0 kW) sanding motor with sanding module	-	S
33	Softstart for 7.5kW motor	O	-
34	Softstart for 15 kW motor	-	O
10	STAR-delta-START	S	S
36	Switch contact for gate control (price/piece)	O	O
	Ampage meter for monitoring the electrical load on the units	S	S
	Automatic sanding-belt brake	S	S
	Sanding unit and sanding cushion		
	Combination unit CU (contact roller and sanding cushion), hardness of the contact roller C 85° Shore, Digital grain compensation can be chosen from the control panel	S	-
	Contact-roller unit, hardness of the contact roller C 85° Shore, Digital grain compensation can be chosen from the control panel	-	S
	Sanding pad unit (sanding pad)	-	S
300	Electro-pneumatic sanding cushion EP	S	S
	Sanding width 950 mm	S	-
	Sanding width 1100 mm	-	S
	<b>Sanding height 3–170 mm</b>	S	S
	Sanding belt is oscillated electro-pneumatically	S	S
	Electronic run-off protection for the sanding belt	S	S
	Pneumatic tensioning of the sanding belt	S	S
	Sanding belt 970 x 1700 mm (width x length)	S	-
	Sanding belt 1120 x 1900 mm (width x length)	-	S
	Feeder table		
	Electronic height adjustment of the feed table in 0.1 mm incremental steps from the control panel	S	S
	Digital display shows the height of the feeder table	S	S
16	Inverter controlled variable feed speed of 2.5-10 m/min, selected from the control panel	S	S
	Mechanical vibration-absorbing rubber pressure rolls	S	S
	Hand guard and over-thickening protection for the workpiece	S	S
	Through feed		
35	Measuring device for the workpiece thickness on the feed table	O	O
	General		
86	Preparation for min. transport width 800 mm	O	-
	Machine packing dimensions in mm (length x width)	1400 x 1350 x 1900	1600 x 1550 x 2050
	Extraction connector Ø in mm	1x 120	2x 160
	Weight kg (with standard configuration)	800	1150
	Additional units		
25	Tynex texturing brush unit 5.5 kW (7.5 PS) with texturing brush K 60 D=200 mm	-	O
26	Quick-change system for brushing unit (#25)	-	O
27	Additional Scotch-Brite brush D=200 mm (#25+26) (!28)	-	O
28	Additional Tampico cleaning brush D=200 mm (#25+26) (!27)	-	O
29	Cleaning brushing unit at the machine outlet D=150 mm (no changing system for additional brushes possible)	-	O
30	Scotch Brite brushing unit at the machine outlet D=150 mm (no changing system for additional brushes possible)	-	O
	Important Accessories		
85	Double-sided roller table extension 200 mm	O	O
221	Preparation for Container Transport	O	O