

# A3 26, A3 31, A3 41

	A3 26	A3 31	A3 41	A3 41A	A3 41D
POS					
Electrics					
001	3x 400 V motor voltage	-	S	S	S
003	1x 230 V motor voltage, motor 4.0 HP (3.0 kW) S6/40%	-	O	O	O
003	1x 230 V motor voltage, motor 2.6 HP (1.6 kW) S6/40%	S	-	-	-
004	50 Hz motor frequency	S	S	S	S
005	60 Hz motor frequency	O	W	W	W
007	Motor 4.0 HP (3.0 kW) S6/40%	-	S	-	-
008	Motor 5.5 HP (4.0 kW) S6/40%	-	-	S	S
28	Additional emergency stop	O	O	O	O
Surface Planer and Cutterblock					
42	3 knife quick-change, self-setting cutterblock system	S	S	S	S
43	3 knife standard-knife cutterblock	-	O	O	O
44	Silent-POWER spiral cutterblock	O	O	O	O
	Number of knives - Silent-POWER spiral cutterblock	39	47	62	62
	Maximum depth of cut in mm	4 mm	4 mm	4 mm	4 mm
	Surface planing width in mm	260 mm	310 mm	410 mm	410 mm
	Surface planer table length in mm	1120 mm	1400 mm	1800 mm	1800 mm
	Planer fence tilting from 90°-45°, anodised	S	S	S	S
	Length of surface planer fence in mm	750 mm	1100 mm	150 x 1100 mm	150 x 1100 mm
Thicknessing planer unit					
	Thicknessing planing width in mm	254 mm	306 mm	406 mm	406 mm
	Thicknessing table length in mm	540 mm	540 mm	600 mm	600 mm
	Min. workpiece length in mm	145	145	145	145
	Thicknessing height min.-max. 4-225 mm	S	S	S	S
	Maximum depth of cut in mm	4 mm	4 mm	4 mm	4 mm
	Synchronized feeder drive 6 m/min. (50 Hz)	S	S	S	S
Mortising Unit					
190	Mortising table	O	O	O	O
191	Mortising chuck 0-16 mm	O	O	O	O
General					
	Extraction size Ø	120 mm	120 mm	120 mm	120 mm
	Weight, kg (with average equipment)	245	290	400	340
Important Accessories					
210	Rolling carriage without lifting bar	O	O	O	O
211	Lifting bar	O	O	O	O
221	Preparation for Container Transport	O	O	O	O
	1/1-202 - Digital clock with 0.1 mm resolution, counter-clockwise counting. pitch 2mm	O	O	O	O
	12.1.311 - ALU - system - hand wheel	O	O	O	O
	500-157 - Table extension assembly set 260 mm	O	-	-	-
	500-102 - Table extension assembly set 310 mm	-	O	-	-
	500-151 - Table extension assembly set 410 mm	-	-	O	O
	500-101 - Table extension, aluminium, width 150 mm, length 400 mm	O	O	O	O