

K4 perfrom

		K4 perform
POS		
	Electrics	
001	3x 400 V motor voltage	S
002	3x 230 V motor voltage	W
003	1x 230 V motor voltage, motor 4.0 HP (3.0 kW) S6/40%	O
004	50 Hz motor frequency	S
005	60 Hz motor frequency	W
008	Motor 5.5 HP (4.0 kW) S6/40%	S
009	Motor 7.5 HP (5.5 kW) S6/40%	O
28	Additional emergency stop	O
	Saw Unit	
	Main sawblade dia. 250–315 mm, Saw unit speed 4800 rpm	S
	Saw blade tilting from 90°–45°, Max. cutting height 103 mm	S
	Saw-spindle moulder table in mm	830 x 430 mm
77	Rip capacity continuously adjustable 49" (1250 mm)	S
81	Swing away overhead saw guard	O
82	Preparation for Dado tooling up to 3/4" (19.5 mm) width	O
88	Fine adjustment for professional rip fence	O
75	Scoring unit, Motor 1.0 HP (0.65 kW)	S
	Anodised Format Sliding Table	
134	Format sliding table 3200 mm, cutting length 3200 mm with edging shoe*	S
	Outrigger Tables and Crosscut Fences	
161	Outrigger table 1290	S
163	Precision mitre guide index system (#160/161)	O
167	Crosscut fence 2600 mm for outrigger 1290	S
169	Crosscut fence 2600 mm for outrigger table, "X-Roll"	O
	Weight	
	Weight, kg (with average equipment) net/gros	550/620 kg
	Important Accessories	
221	Preparation for container transport	O
223	Heat treated palette according to IPPC regulations	W
	.SET-HA20-1 - SET: Display clock with system hand wheel - (for circular saw unit)	O