

POS		
	Electrical setup	
001	3x 400 V	S
002	3x 230 V motor voltage	W
003	1x 230 V, motor power 4.0 HP (3.0 kW)*	O
004	50 Hz	S
005	60 Hz	W
006	4.0 HP (3.0 kW)*	S
007	5.5 HP (4.0 kW)*	O
28	Additional emergency stop	O
	Cutterblock	
30	Surface planing width in mm	310
	Maximum depth of cut in mm	5
33	Surface planer fence anodised	S
34	Additional table for planer fence	S
36	Planer guard EURO "Standard"	S
37	Planer guard EURO "Comfort"	O
38	2-knife Felder-system cutterblock	S
39	4-knife Felder-system cutterblock	O
44	Silent-POWER spiral cutterblock	O
	Number of knives - Silent-POWER spiral cutterblock	47
	Thickness Planer and Feed Drive	
50	Thickness planing width in mm	306
	Min. workpiece length in mm	190
	Maximum depth of cut in mm	5
51	Digital display for thicknessing height in mm	O
52	Digital display for thicknessing height in inch	O
56	Synchronized feeder drive 6 m/min	S
	Mortising Unit	
191	Mortising chuck, clamping range 0–16 mm	O
189	Mortising table	O
190	Mortising table, heavy professional execution	O
194	Transport unit for mortising table heavy (#190)	O
	General	
	Working height in mm	890
	Min. transport width in mm	700
	Extractor connection port diameter in mm on Planer/Thicknesser	120
	Weight kg (with standard configuration)	400
	Important Accessories	
210	Rolling carriage	O
211	Coupling system for table extension (thicknessing or spindle moulder table, 1 pcs)	O
223	IPPC	W
	Transport	
221	Preparation for container	W